

FAAC-104200



422 CBAC 1L 230V HYDRAULIC OPERATOR WITH LOCK

The FAAC 422 automated system for swing leaf gates consists of an enbloc composed of an electric pump and a hydraulic piston which transmits drive to the leaf. The models with a hydraulic locking do not require installation of electric locks, as they guarantee mechanical locking of the leaf when the motor is not operating.

FEATURES

- A wide versatile range
- Maximum anti-crushing safety thanks to an exclusive hydraulic device
- Anti-corrosion cover with high weather resistance
- Key protected, release device
- 422 CBC-CBAC-CBACS - max length 1.8m

TECHNICAL INFORMATION

- Power supply voltage: 230Vac (+6% - 10%) 50(60) Hz
- Power: 220 W
- Absorbed current: 1A
- Motor rotation speed: 1400 RPM
- Rod Extension speed: 1.3cm/s
- Pump flow rate: 1 l/min
- Traction and thrust force: 0 to 500 daN
- Operating ambient temperature: -20°C - + 55°C
- Thermal protection on motor winding: 120°C
- Weight: 7kg
- Type of oil: FAAC HP Oil
- Protection Class: IP 55
- Dimensions: 987(L) x 120(D) x 85(H) mm – pedestrian
827(L) x 120(D) x 85(H) mm