

## FAAC-104415



### **415 230V ELECTRO-MECHANICAL OPERATOR**

FAAC 415 230v Operator. Suitable for residential swing-leaf gates, max single leaf gate length 3m (415) and 4m (415 L)

#### **FEATURES**

- Available with a 300mm (max leaf 3m) and 400mm (max leaf 4m) rod stroke
- LS versions are equipped with opening and closing limit switches to ensure the gate opens and closes fully whatever the weather
- These energy efficient-operators are highly adjustable to allow maximum flexibility in installation dimensions
- Horizontal exit for cables to allow low installation

#### **TECHNICAL INFORMATION**

- Power supply voltage: 230Vac (+6% - 10%) 50(60) Hz
- Power: 300 W
- Absorbed current: 1.3A
- Thermal protection: 140°C
- Capacitor: 8µF
- Thrust: 300 daN
- Travel: 300mm
- Rod speed: 1.6cm/sec
- Leaf max width: 3m\*
- Use frequency at 20°C: 30%
- Approx min cycle/hour at 20°C: 30
- Operating ambient temperature: -20°C - +55°C
- Operator weight: 7.8kg
- Operator length: 840
- Operator dimensions: 835(L) x 105(H) x 148(W)mm
- Protection class: IP44