

NICE-KIT-ROBUS-3



24V SLIDING GATE KIT UP TO 1000KG

This is an easy to install sliding gate kit which is suitable for gates up to 1000kg in weight.

FEATURES

- Suitable for heavy gates
- Quiet system (gear on motor bearings)
- Adaptable to climatic conditions
- Adjustable acceleration and deceleration at opening and closing Kit does not include drive rack
- The Nice BlueBUS technology, enables to power and control a maximum of seven couples of photocells from the MoonBus series using two wires only
- The control unit and PS124 buffer battery (optional) can be connected by means of a simple connector and can be housed directly inside the motor
- RB400, RB600 and RB1000 are equipped with a temperature sensor: adapt the motor power to the climatic conditions and at the same time thermal cut-out
- A master/slave selection automatically synchronises two motors, meaning it is possible to automate 2-leaf sliding gates set opposite each other
- Obstacle detection system and automatic programming of working times
- Self-diagnosis by means of a flashing light
- 8 programming levels
- Acceleration and deceleration can be adjusted at the beginning and end of each opening and closing manoeuvre
- Base and release in pressure die cast with easy to open handle

TECHNICAL INFORMATION

- Power supply (Vac 50 Hz): 230
- Absorption (A): 2.3
- Power (W): 450
- Speed (m/s): 0.28
- Force (N): 900
- Work cycle (cycles/hours): 50
- Protection level (IP): 44
- Working temp: -20°C ÷ +50°C
- Dimensions (mm): 330 x 210 x 303
- Weight: 13kg