

## RT-BE20/200




## BRUSHLESS MOTOR FOR SWING GATES UP TO 2.8M

Low voltage brushless electromechanical actuator, for super intensive use, with native encoder on board, irreversible, ideal for swing gates with leaves up to 2.8m with mechanical stops on opening and closing.

### FEATURES

- Electromechanical actuator BRUSHLESS
- Low voltage
- Super intensive use, with native encoder onboard
- Irreversible
- Ideal for swing gates with leaf up to 2.8m length, with mechanical stopper in opening and closing



QUOTA W mm	QUOTA W mm	ANGOLI APERTURA
110	100	180°
110	200	180°
130	100	180°
130	200	180°
150	100	180°
150	150	135°
150	150	110°
150	200	180°
180	100	110°
180	100	180°
QUOTA W 866 mm	QUOTA W 105 mm	QUOTA W 155 mm
100	270	62

### TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 24V
- Power rating: 200W
- Frequency of use: Intensive use
- Thrust: 100 - 2200N
- Operating temperature: -20 C° +55 C°
- Protection level: IP43
- Reductor Type: Irreversible
- Manoeuvre speed: 1.66 cm/s
- Opening time at 90°: 15-25 s
- Stroke: 400 mm
- Limit switch: Mechanical stopper in opening and closing
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Operating cycles per day (opening/closing - 24 hours no stop): 800
- Maximum dimension product in mm (L x W x H): 867 x 105 x 155
- Product weight packed (Kg): 7.9

## RELATED PRODUCTS



**RT-BE20/200/HS**



**RT-MC781**



**RT-KT206**