


RT-BI/006



BIONIK 6M BARRIER UNIT

36Vdc BIONIK BRUSHLESS barrier for 6 meter boom, with control unit and on-board native encoder, complete with a fastening base with tie rods and screws and boom fastening flanges.

FEATURES

- Automatic Barrier Brushless 36Vdc
- Super intensive use up to 6 meters, with operator and built-in digital control panel and absolute encoder on board.

TECHNICAL INFORMATION

- Barriers: Up to 6m long
- Power line supply: 230V AC - 50Hz
- Motor power supply: 36Vdc
- Electrical absorption: max 15A
- Power rating: 220W
- Frequency of use: Super intensive use
- Torque: 10 - 300 N m
- Operating temperature: - 20 + 55 C°
- Protection level: IP54
- Reductor Type: Irreversible
- Opening time at 90°: 4 ÷ 8 (sec)
- Onboard control unit: CTRL Digital Controller 36Vdc
- Encoder: Digital native encoder + magnetic digital SENSORED, 4096 PPR
- Accessories power supply: 24Vdc
- Release system: European Key cylinder
- Batteries recovery: Available (optional)
- BUS synchronization Master/Slave: Yes
- Operating cycles per day (opening/closing - 24 hours no stop): 4000 cycles
- Maximum dimension product in mm (L x W x H): 380 x 270 x 1237
- Product weight packed (Kg): 74