

## RT-KIT-SMARTY4/HS-S



### 36V SMARTY SINGLE HIGH SPEED KIT UP TO 4M GATE

Low voltage HIGH SPEED Irreversible BRUSHLESS electro mechanical gear motor for extremely heavy duty. For swing gates with gate leaf up to 4m

#### FEATURES

- Low voltage
- High speed
- Irreversible
- BRUSHLESS electromechanical gear motor for extremely heavy duty
- For swing gates with gate leaf up to 4m

#### Kit Composition:

1x Edge/1 Digital control board  
1x Smarty 4/HS Brushless Motor  
2 x E80/TX52R/2 Remote controls  
1x H93 receiver  
1x R90/F2ES Photocells  
1x Fifty Light or Antenna

#### TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 36V
- Power rating: 200W
- Frequency of use: Intensive use
- Thrust: 600 - 4500N
- Operating temperature: -20 C° +55 C°
- Protection level: IP44
- Reductor Type: Irreversible
- Manoeuvre speed: 2 - 1 cm/s
- Opening time at 90°: 15-25 s
- Stroke: 370mm
- Limit switch: Mechanical stopper in opening and closing
- Encoder: Digital native encoder SENSORLESS 48 PPR
- Operating cycles per day (opening/closing - 24 hours no stop): 1000
- Maximum dimension product in mm (L x W x H): 1162 x 116 x 165
- Product weight packed (Kg): 16.5