

RT-SET-BH23/284



BRUSHLESS DOUBLE ARTICULATED SHORT ARM SWING GATE KIT

SET of 2 electromechanical articulated motor, BRUSHLESS, low voltage, super intensive use, with native encoder onboard, irreversible, ideal for swing gates with leaf up to 2.8 m of length, with mechanical stopper in opening and closing and with standard version of short arms.

FEATURES

- SET Electro mechanical articulated motor
- BRUSHLESS
- Low voltage
- Super intensive use
- With native encoder on board
- Irreversible
- Ideal for swing gates with leaf up to 2.5 metres of length
- With mechanical stopper in opening and closing and with standard version of short arms

TECHNICAL INFORMATION

- **Power line supply:** 230V AC - 50Hz
- **Motor power supply:** 24V
- **Power rating:** 160W
- **Frequency of use:** Intensive use
- **Torque:** 50 - 280 N m
- **Operating temperature:** -20+55° C
- **Protection level:** IP43
- **Reductor Type:** Irreversible
- **Manoeuvre speed:** 1 - 1,9 Rpm
- **Opening time:** 12-20 s
- **Limit switch:** Mechanical stopper in opening and closing
- **Encoder:** Digital native encoder SENSORLESS 48 PPR
- **Operating cycles per day (opening/closing - 24 hours no stop):** 1900
- **Maximum dimension product in mm (L x W x H):** 230 x 190 x 284
- **Product weight packed:** 31.1Kg