

RT-SET-BI/008GO/DX



DELUX 8M BIONIK BARRIER KIT

36Vdc Bionik brushless barrier for 8 meter boom, with control unit and on-board native encoder, complete with a fastening base with tie rods and screws and boom fastening flanges. Heavier edition unit.

FEATURES

- Automatic Barrier Brushless 36Vdc
- Super intensive use up to 8 meters
- With operator and built-in digital control panel and absolute encoder on board

TECHNICAL INFORMATION

- Barriers: Up to 8 m long
- Power line supply: 230V AC - 50Hz
- Motor power supply: 36Vdc
- Electrical absorption: max 18A
- Power rating: 300W
- Frequency of use: Super intensive use
- Torque: 10 - 400 N m
- Operating temperature: - 20 + 55°C
- Protection level: IP54 Reductor
- Type: Irreversible
- Opening time at 90°: 9 ÷ 29 (sec)
- Onboard control unit: CTRL Digital Controller 36Vdc
- Encoder: Digital native encoder + magnetic digital SENSORED, 4096 PPR
- Accessories power supply: 24Vdc
- Release system: European
- Key cylinder Batteries recovery: Available (optional)
- BUS synchronisation
- Master/Slave: Yes
- Operating cycles per day (opening/closing - 24 hours no stop): 2500 cycles
- Maximum dimension product in mm (L x W x H): 500 x 270 x 1237
- Product weight packed (Kg): 95