

## RT-SET-R21/353



### 230V DOUBLE UNDERGROUND KIT UP TO 3.5M

230v electromechanical underground kit, ideal for swing gates with leaf up to 3.5 meters of length. Standard version with 2 meters cable.

#### FEATURES

- Set of 2 electromechanical underground motors 230V AC
- Irreversible
- Ideal for swing gates with leaf up to 3.5 metres of length
- Standard version with 2 meters cable
- Kit Composition:
  - 1x H70/200ac Controller
  - 2x R21/351 Brushless Motors
  - 1x RL650 Release shoes
  - 2x FU100 Galvanised Foundation Boxes
  - 2x E80/TX52R/2 Remote controls
  - 1x R90/F2ES Photocells
  - 1x Fifty Light or Antenna

#### TECHNICAL INFORMATION

- Power line supply: 230V AC - 50Hz
- Motor power supply: 230V AC
- Power rating: 200W
- Frequency of use: 30%
- Torque: 300 N m
- Operating temperature: -20+55°C
- Protection level: IP67
- Reductor Type: Irreversible
- Manoeuvre speed: 1.2 Rpm
- Opening time at 90°: 19s
- Motor thermal protection: 150°C
- Limit switch: Mechanical stoppers
- Encoder: Optional as an accessory
- Maximum opening: 105°(optional 125° - 360°)
- Power supply cable length: 2m
- Bearing on main shaft: Standard
- Maximum dimension product in mm (L x W x H): 345 x 224 x 144
- Product weight packed (Kg): 67