



sales@specialized-security.co.uk
www.specialized-security.co.uk

01763 274 223

NICE-KIT-ROBUS-1



Nice



24V SLIDING GATE KIT UP TO 600KG

This is an easy to install sliding gate kit which is suitable for gates up to 600kg in weight.

FEATURES

- A quiet and reliable sliding gate kit that is easy to install
- The Robus 600 is suitable for light residential gates.
- It is adaptable to climatic conditions and has adjustable acceleration and deceleration at opening and closing.
- User-friendly: the Nice BlueBUS technology, enables to power and control a maximum of 7 pairs of photocells from the MoonBus series using two wires only.
- Self closing: can be programmed to self close.
- Practical: the control unit and PS124 buffer battery (optional) can be connected by means of a simple connector and can be housed directly inside the motor.
- Advanced: Robus 600 & 1000 are equipped with a temperature sensor which adapts the motor power to the climatic conditions and at the same time the thermal cut-out. A master/slave selection automatically synchronises 2 motors. This means it is possible to automate 2-leaf sliding gates set opposite each other.
- Intelligent: thanks to the obstacle detection system and automatic programming of the working times. Self-diagnosis by means of a flashing light. 8 programming levels.
- Safe: acceleration and deceleration can be adjusted at the beginning and end of each opening and closing manoeuvre.
- Sturdy: base and release in pressure die cast with easy to open handle.
- Very quiet: gear motor on bearings.

TECHNICAL INFORMATION

- Power supply (Vac 50 Hz): 230
- Absorption (A): 2.5
- Power (W): 515
- Speed (m/s): 0.31
- Force (N): 600
- Work cycle (cycles/hour): 40
- Protection level (IP): 44
- Working temp: 20°C ÷ +50°C
- Dimensions (mm): 330 x 210 x 303
- Weight: 11kg