

EM02-ECO




SLIM MONITORED ECO FRIENDLY MAGLOCK 12/24VDC

Slim single lock-monitored ECO friendly magnetic lock. Its compact design makes it ideal for most indoor applications where 275kg holding force is sufficient. Monitoring provides LED lock status indication and relay contacts for signalling.

FEATURES

****Running cost saving of £12.53 per annum per mag V's the EMO2****

(Correct at time of printing and based on home tariff cap)



- Voltage input: 12Vdc-24Vdc (auto selectable)
- Compatible with existing maglock and associated bracket range
- MOV provides spike and surge protection
- Fail-safe operation (power to lock); Anti-residual magnetism protection
- Top-plate, armature-plate and fixings included
- Slim design, Surface mount with Silver anodised aluminium finish
- Lock monitoring with Hall bond sensor & LED monitor door status

Recent customer quoted as saying *"I will ensure that we use the ECO range from now on, the other advantage to us is, as we supply Access control units that control up to 8 doors the total reduction in current is significant and reduces the Power Supply requirements or least means they run cooler and more reliably"*.

TECHNICAL INFORMATION

- Holding force: up to 275kg (600lbs)
- Low consumption energy
- Current draw = 250mA @ 12Vdc / 130mA @ 24Vdc
- Voltage tolerance: +/- 5%; Operating temp: -10°C to +55°C
- Zero residual: Mechanical (Kick off button)
- Weight: 2.5kg approx; Relay: COM/NO/NC

RELATED PRODUCTS

ECO ECO
FRIENDLY



EM05-ECO

ECO ECO
FRIENDLY



EM20-ECO



EM300ZLG

FIRE TESTED



EM02-FIRE