

## EXM12-24-UN



### **STANDARD UNMONITORED S/STEEL WEATHERPROOF MAGLOCK 12/24VDC**

This stainless steel external maglock is ideal for outdoor use (e.g. gates) due to its weatherproof construction and attachment for connection to conduit. Suitable for 12V or 24Vdc operation.

#### **FEATURES**

- Stainless steel casing
- Weatherproof
- Dual voltage (12Vdc or 24Vdc selectable)
- Anti-residual magnetism feature
- Fail-safe (=power to lock)
- Side or face fixings

#### **TECHNICAL INFORMATION**

- Voltage: 12Vdc or 24Vdc (adjustable)
- Holding Force: 545kg (1200lbs)
- 4 Wires
- Lock Size: 222L x 62W x 38H(mm)
- Armature Plate: 195L x 61W x 15H(mm)
- Current Draw: 12Vdc/420mA 24Vdc/210mA
- Surface Temp: ?20°C
- Operating Temp: -10°C ~ 55°C (14°F-131°F)
- Suitable Humidity: 0~90%(non-condensing)
- Finishes for shell: Stainless steel
- Finishes for magnetic face: Zinc
- Finishes for armature: Zinc
- Weight: 4.5kg
- 20mm male conduit connection
- Cable length: 300mm

## **RELATED PRODUCTS**



**EM500ZLW**



**KGG300SG-WP**



**SPB004S(W)**