

EXM12-24-UN



STANDARD UNMONITORED S/STEEL WEATHERPROOF MAGLOCK 12/24VDC

This stainless steel external maglock is ideal for outdoor use (e.g. gates) due to its weatherproof construction and attachment for connection to conduit. Suitable for 12V or 24Vdc operation.

FEATURES

- Stainless steel casing
- Weatherproof
- Dual voltage (12Vdc or 24Vdc selectable)
- Anti-residual magnetism feature
- Fail-safe (=power to lock)
- Side or face fixings

TECHNICAL INFORMATION

- Voltage: 12Vdc or 24Vdc (adjustable)
- Holding Force: 545kg (1200lbs)
- 4 Wires
- Lock Size: 222L x 62W x 38H(mm)
- Armature Plate: 195L x 61W x 15H(mm)
- Current Draw: 12Vdc/420mA 24Vdc/210mA
- Surface Temp: ?20°C
- Operating Temp: -10°C ~ 55°C (14°F-131°F)
- Suitable Humidity: 0~90%(non-condensing)
- Finishes for shell: Stainless steel
- Finishes for magnetic face: Zinc
- Finishes for armature: Zinc
- Weight: 4.5kg
- 20mm male conduit connection
- Cable length: 300mm

RELATED PRODUCTS



EM500ZLW



KGG300SG-WP



SPB004S(W)