

**EM02**




**SLIM MONITORED MAGLOCK  
12/24VDC**

Slim single lock-monitored magnetic lock. Its compact design makes it ideal for most indoor applications where 275kg holding force is sufficient. Monitoring provides LED lock status indication and relay contacts for signalling.

**FEATURES**

- MOV provides spike and surge protection
- Fail-safe operation (power to lock)
- Anti-residual magnetism protection
- Top-plate, armature-plate and fixings included
- Slim design
- Dual voltage 12Vdc or 24Vdc (selectable)
- Surface mount
- Silver anodised aluminium finish
- Lock monitoring



**TECHNICAL INFORMATION**

- Holding force: up to 275kg (600lb)
- Current draw = 500mA @ 12Vdc / 250mA @ 24Vdc
- Voltage tolerance: +/- 15%
- Operating temp: -10°C to +55°C
- Humidity: 0-95% non-condensating
- Weight: 2kg approx.
- Red/Green LED indicator
- Relay: COM/NO/NC (1A@24Vdc)

**RELATED PRODUCTS**

|  |  |  |  |
|--|--|--|--|
|  <p><b>EM300ABP</b></p> |  <p><b>EM300ZLG</b></p> |  <p><b>NT200-S</b></p> |  <p><b>EM02-ECO</b></p> |
|--|--|--|--|